



### ORDERING INFORMATION

AFP - [ ] [ ] [ ] 0 0

**Actuator**

- N NPT Ports
- G G Ports

**Port Position**

- 1 Port Position (Shown)
- 2 Port Position
- 3 Port Position
- 4 Port Position

**Switch**

- E Efector (STD) (Weld Immune)
- B Balluff
- T Turck
- S Sick

NOTE: Switch is 90 degrees from port position, either side

NOTE: LOAD PART RIGID (CYLINDER EXTENDED) UNLOAD PART FLOATING (CYLINDER RETURNED)  
 OPER PRESSURE = 60 psi MIN - 120psi MAX  
 WEIGHT = 4.5lbs [2.04kg]

	<small>NOTICE: THIS DRAWING IS PROPERTY OF E&amp;E CUSTOM PRODUCTS INCLUDING THE PRINCIPLES OF THE DESIGN INVOLVED, AND IS SUBMITTED WITH AGREEMENT THAT IT IS NOT TO BE REPRODUCED, COPIED, OR LOANED, IN PART OR WHOLE, ACCEPTANCE OF THIS DRAWING WILL BE CONSTRUED AS AN AGREEMENT TO THE ABOVE</small>		
	TITLE 50mm BORE PNEUMATIC FLOAT PIN		
	PART NO.		
	DRAWN BY:	CHK'D BY:	APPR'D BY:
	DATE:	DATE:	DATE:
7200 MILLER DR. WARREN, MI 48092 EE-CP.COM	SCALE: 1/2 SHT 1 OF 1	DWG. NO. AFP TEMPLATE	