



SYM	CHANGES	DATE	BY
-----	---------	------	----

ORDERING INFORMATION

ALP50- [] [] [] N [] S [] O O

- Stroke**
 - 025 25mm Stroke
 - 050 50mm Stroke
- Actuator**
 - N Pneumatic - NPT Ports
- Pin**
 - C Conical
 - F Flat
- Spring**
 - 0 None
 - S Spring
- Switch**
 - S Sick

NOTE: Switch is 90 degrees from port position, either side

25mm STROKE USES REMOVABLE CYLINDER STOP TUBE
 OPERATING PRESSURE - MIN 60psi = 467.3lbf [211.9kgf] EXT FORCE - 284.4lbf [129kgf] RETRACT FORCE
 MAX 120psi = 934.5lbf [423.8kgf] EXT FORCE - 568.8lbf [258kgf] RETRACT FORCE
 SPRING FORCE EXTEND = 100lbf [45.4kg] 25mm STROKE - 80lbf [36.3kg] 50mm STROKE - 115lbf [52.2kg] RETURNED
 LOCKOUT LOAD CAPACITY = 5,000lbs (2,267.6kg)
 WEIGHT = 18lbs (8.2kg)

	<small>NOTICE: THIS DRAWING IS PROPERTY OF E&E CUSTOM PRODUCTS INCLUDING THE PRINCIPLES OF THE DESIGN INVOLVED, AND IS SUBMITTED WITH AGREEMENT THAT IT IS NOT TO BE REPRODUCED, COPIED, OR LOANED, IN PART OR WHOLE, ACCEPTANCE OF THIS DRAWING WILL BE CONSTRUED AS AN AGREEMENT TO THE ABOVE</small>		
	TITLE 50mm PNEUMATIC LOCKOUT		
	PART NO.		
	DRAWN BY: EE	CHK'D BY: EC	APPR'D BY: TT
	DATE: 3/21/2023	DATE: 10/19/2023	DATE: 10/19/2023
7200 MILLER DR. WARREN, MI 48092 EE-CP.COM	SCALE: 1/4	DWG. NO. ALP50_TEMPLATE-GESTAMP	
SHT 1	OF 1		