SYM	CHANGES	DATE	BY



ORDERING INFORMATION

ALP25-[ ][ ][ ][ ][ ][ ]0 0

Stroke
- 025 25mm Stroke
- 050 50mm Stroke

Actuator
- N Pneumatic - NPT Ports
- G Pneumatic - G Ports

Pin
- C Conical
- F Flat

Spring
- 0 None
- S Spring

Switch
- E Efector (Std) Weld Immune
- B Balluff
- T Turck
- S Sick

NOTE: Switch is 90 degrees from port position, either side



CONICAL NOSE
LOCATIONAL USE



FLAT NOSE
LOCKOUT USE





25mm STROKE USES REMOVABLE CYLINDER STOP TUBE
OPERATING PRESSURE - MIN 60psi = 182lbf [82.5kgf] EXT FORCE - 137lbf [62.1kgf] RETRACT FORCE
MAX 120psi = 362lbf [164.2kgf] EXT FORCE - 274bf [124.3kgf] RETRACT FORCE
SPRING FORCE EXTEND = 30lbf [13.6kg) 25mm STROKE - 20lbf [9.1kg) 50mm STROKE - 40lbf [18.1kg) RETURNED
LOCKOUT LOAD CAPACITY = 2,500lbs (1,133kg)
WEIGHT = 6.25lbs (2.8kg)

E & E CUSTOM PRODUCTS

7200 MILLER DR.
WARREN, MI 48092
EE-CP.COM

NOTICE: THIS DRAWING IS PROPERTY OF E&E CUSTOM PRODUCTS INCLUDING THE PRINCIPLES OF THE DESIGN INVOLVED, AND IS SUBMITTED WITH AGREEMENT THAT IT IS NOT TO BE REPRODUCED, COPIED, OR LOANED, IN PART OR WHOLE, ACCEPTANCE OF THIS DRAWING WILL BE CONSTRUED AS AN AGREEMENT TO THE ABOVE

TITLE: 25mm PNEUMATIC LOCKOUT		
PART NO.		
DRAWN BY:	CHK'D BY: EC	APPR'D BY: TT
DATE:	DATE: 10/19/2023	DATE: 10/19/2023
SCALE: 1 / 2	DWG. NO. ALP25 TEMPLATE	
SHT 1 OF 1		